



Sidewalk Width Requirements

Classification of Street and Zoning District	Minimum Width
Local and collector streets in residential districts	5 feet
Local and collector streets in B-3, B-5, IN-1, IN-2, I-1, I-2 and I-3 districts	6 feet
Local and collector streets in B1 districts	6 feet where buildings are set back more than 10 feet 8 feet where buildings are set back 10 feet or less
Arterial streets	6 feet
B-4 districts	8 feet

NOTES:

1. FOR ALL STREET CLASSIFICATIONS:
AGGREGATE BASE SHALL BE SEALED WITH LIQUID BITUMINOUS MATERIAL CRS-2 AT THE RATE OF 0.3 GALLONS PER SQUARE YARD AND COVERED WITH No. 78 STONE AT THE RATE OF 15 POUNDS PER SQUARE YARD. THIS IS NOT REQUIRED IF BASE ASPHALT OF 4" OR GREATER IS INSTALLED.

2. THE DESIGN DEPTHS SHOWN ABOVE ARE MINIMUM REQUIREMENTS. ACTUAL DEPTHS SHALL BE DETERMINED THROUGH CBR TESTING AND ANALYSIS.

THE CITY OF LYNCHBURG
 TYPICAL CURB and GUTTER
 STREET SECTION
 USE WITH THE CITY OF LYNCHBURG STANDARD SPECIFICATIONS ONLY

SCALE:
 NOT TO SCALE
 REVISION DATE:
 4-2023

DETAIL #
25.01
 SHEET #:
 3 OF 3